

1.	IDENTIFICATION			
	Product Identification			
	Product Name	Human NF-kB Array C2		
	Catalog Number	AAH-NFKB-2		
	Kit Components			
	Usage			
	This product is furnished for LABORATORY	RESEARCH USE ONLY. Not for diagnostic or therapeutic use.		
	Supplier Identification			
	Company	RayBiotech, Inc.		
		3607 Parkway Lane, Suite 100		
		Norcross, GA 30092		
		USA		
	Telephone	1-888-494-8555 (Toll Free); 770-729-2992		
	Fax	770-206-2393		
	Website	www.RayBiotech.com		
	Email	info@raybiotech.com		
	Emergency Telephone Number			
	Emergency Phone #	1-888-494-8555		

2. HAZARDS IDENTIFICATION

Hazardous Ingredients

1. The 2X Cell Lysis Buffer contains Triton-X-100.

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

Triton-X-100 (Lysis Buffer): Skin Corr./Irrit. 1A (H314); Acute Oral Toxicity

GHS Label Elements

Hazard Pictograms



Signal Word/s	Warning
Hazard Statements	Triton-X-100 (Lysis Buffer): Causes skin irritation (H315); Causes serious eye irritation (H319); Harmful if swallowed (H302)
Response	 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. EYE CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. SKIN CONTACT: Take off immediately all contaminated clothing. Rinse skin with water/shower. INHALATION: Move to an outside area and breath fresh air. Clear the nose by blowing.

Storage	Not applicable.
Disposal	Not applicable.

Hazards not otherwise classified

None known.

Ingredient Name % CAS Numbers/other Triton-X-100 1-3 9002-93-1

4. FIRST-AID MEASURES

Description of Necessary First Aid Measures

Eye ContactImmediately flush eyes with plenty of water, occasionally lifting the upper and lower eyeli for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medica if irritation occurs.	
Skin Contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing and clean shoes before reuse.
Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If that fumes are still present, the rescuer should wear an appropriate mask or self-combreathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest or artificial respiration or oxygen by trained personnel. It may be dangerous to the personaid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effer are severe. If necessary, call a poison center or physician. If unconscious, place in reposition and get medical attention immediately. Maintain an open airway. Loosen tig such as a collar, tie, belt or waistband.	
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Potential Acute Health Effects

Eye Contact	Triton-X-100 (Lysis Buffer): Causes serious eye irritation (H319)
Skin Contact	Triton-X-100 (Lysis Buffer): Causes skin irritation (H315)
Ingestion	Triton-X-100 (Lysis Buffer): Harmful if swallowed (H302)

Over-Exposure Signs/Symptoms

No specific data.

Notes to Physician

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific Treatments

No specific treatment

Protection of First-Aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

5. FIRE FIGHTING MEASURES

Extinguishing Media	Use an extiguishing agent suitable for the surrounding fire, such as water spray, carbon dioxide, dry chemical power or appropriate foam. Prevent contact with skin and eyes.
Chemical Hazards from Fire	In a fire or if heated, a pressure increase will occur and the component containers may burst.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For Non- Emergency Personnel	No action shall be taken involving any personal risk or without suitable training.Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For Emergency Responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For Non-Emergency Personnel" above.
Environmental Precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Protective Equipment	Wear respirator, chemical safety goggles, rubber boots and rubber gloves.

Methods and Materials for Containment and Cleaning Up

Small Spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up ifwater- soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large Spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. STORAGE AND HANDLING

Storage

Store the entire kit frozen at -20°C upon arrival.

Handling

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Permissible Exposure Limits (PELs)

This product does not contain any hazardous materials with occupational exposure limits established by theregion specific regulatory bodies.

Appropriate Engineering Controls

Showers Eyewash stations Ventilation systems

Protective Equipment

Wear suitable protective clothing, including gloves, safety glasses, dust mask, and a laboratory coat.

Special Precautions

Not for human or drug use. Not for household use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, colorless
Odor	Odorless
Physical State	Liquid
рН	N/A
Boiling Point	N/A
Melting Point	N/A
Freezing Point	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Specific Gravity	N/A
Evaporation Rate	N/A
Solubility in Water	N/A
Odor Threshold	N/A
Coefficient of Water/Oil Distribution	N/A

10. STABILITY AND REACTIVITY

Chemical Stability

Hazardous Reactions

Stable under normal handling procedures. Under normal conditions of storage and use, hazardous reactions will not occur.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Ingredient Name	Result	Species	Dose		
Triton-X-100	LD50	Oral rat female Oral rat male	707 mg/kg 2140 mg/kg		
Carcinogenicity Not listed		carcinogen by ACGIH, IARC, NTP	, or CA Prop 65		
Sensitization	Not Available				
Mutagenicity	Not available	Not available			
Reproductive Toxicity	Not Available	Not Available			
Specific target organ toxici (single exposure)	ty Not available	Not available			
Specific target organ toxici (repeated exposure)	ty Not available	Not available			
Aspiration hazard Not availa		available			
Likely routes of exposure Routes of entry		y anticipated: Oral, Dermal, Inhalation.			
Potential acute health effect	ts				

	Eye contact	Triton-X-100 (lysis buffer) & Sulfuric Acid (stop solution): Risk of serious damage to eyes.
	Inhalation	
	Ingestion	Triton-X-100 (lysis buffer): Harmful if ingested
	Skin Contact	Triton-X-100 (lysis buffer): Skin irritant or corrosion.
12.	ECOLOGICAL INFORMATION	
	Ecotoxicity	No data available
	Persistence and degradability	No data available
	Bioaccumulation/accumulation	No data available
	Mobility in environmental media	No data available
	Other hazardous effects	May be harmful to the environment, particularly aquatic organisms.
13.	DISPOSAL CONSIDERATIONS	
	Disposal methods	Disposal should be in accordance with applicable national, state, and local laws and regulations. Local regulations may be more stringent than national or state requirements. Verify local and state regulations before discharging into public sewers or landfills. Do not dump into any body of water. Contact a licensed professional waste disposal service for appropriate methods of disposal.
14.	TRANSPORT INFORMATION	
	DOT	Not dangerous goods.
	ΙΑΤΑ	Not dangerous goods.
	ADR	Not dangerous goods.
15.	REGULATORY INFORMATION	
	United States (TSCA)	All ingredients are on the inventory or exempt from listing.
	Canada (DSL / NDSL)	All ingredients are on the inventory or exempt from listing.
	SARA 302 Components	Triton-X-100 (lysis buffer): CAS 9002-93-1
	SARA 313 Components	Triton-X-100 (lysis buffer): Concentration <3%
	SARA 311/312 Hazards	Triton-X-100 (Lysis Buffer): Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation
	California Prop. 65 Components	This product does not contain any Proposition 65 chemicals.
16.	OTHER INFORMATION	
	Disclaimer	The above information was obtained from sources available at the time of revision and believed to be accurate and reliable. The information included is not intended to be all inclusive and should only be used as a guide. RayBiotech shall not be held liable for any damage resulting from use, handling, or contact with the above product.
	Last Revised	September 1, 2020

